CN 94 STRONG CONTACT

Special primer for critical substrates







CN 94 STRONG CONTACT

Special primer for critical substrates

Ceresit CN 94 STRONG CONTACT is a special primer for reliable bonding of floor levelling compounds, ceramic and natural stones on critical substrates.



How it works?

Natural wetting agents – better coverage
without with
wetter wetter

Special **natural wetting agents** provide better coverage and good adhesion on the critical substrate. These liquid softening wetting agents are plasticizing and tackifying resin. Their properties combined with CN 94 wide compatibility, allow for various types of product applications:

- on absorbent and non-absorbent substrates
- on vertical and horizontal ones

Combination of dispersions – durability, flexibility and adhesion

Combination of selected dispersions provides durability, flexibility and adhesion. Particles of different sizes help polymers to penetrate even difficult types of surface, resulting in better overall flexibility. Therefore CN 94 strengthens the substrate surface and improves adhesion.







CN 94 can be applied on:

- floor levelling mortars
- existing ceramic and stone tiles
- painted and non-painted wood derivative substrates (chipboards, OSB, boards)
- anhydrite, cement and mastic asphalt screeds
- prefabricated screed elements (e.g. floor gypsum-fibre board)
- concrete (including vacuum concrete)
- cement, cement-lime and lime plasters
- gypsum and aerated concrete substrates
- heated floor structures

CN 94 is easy to apply:







fast drying



lower consumption



CN 94 is a **concentrate and can be easily diluted** with water. The ratio 1:3 is recommended but depending on the application surface (check the Technical Data for more detailed information). The product has a wide temperature range of application above 5°C.



CN 94 is solvent free and contains a **blue pigment to control the application more easily.** For absorbent surfaces only the amount needed to cover the whole surface should be used, and for non-absorbent surfaces as much as will work.

CN 94 STRONG CONTACT BENEFITS:







HIGHLY CONCENTRATED









STRENGTHENS
THE SUBSTRATE AND
IMPROVES ADHESION

FOR CRITICAL SUBSTRATES
SUCH AS TILES (TILE ON TILE
SYSTEM) AND OSB PLATES



WIDE RANGE OF APPLICATIONS



Henkel CEE

Erdbergstrasse 29 1030 Vienna www.ceresit.com