

08/2022

| | contains | m ² | ft ² | weight |
|------------------|----------|-----------------------|-------------------------|---------|
| 1 pack Impulse | 9 planks | 2,20 m ² | 23.71 ft ² | 15,7 kg |
| 1 pallet Impulse | 56 packs | 123,34 m ² | 1327.61 ft ² | 891 kg |

product specifications

| | |
|-----------------------------------------------------|---------------------------|
| Dimensions | 1288 x 190 mm |
| Total thickness | 8 mm |
| Bevels | 0 |
| Loc System | DuoLoc |
| Level of use according to European standard EN10874 | 23 heavy domestic use |
| | 32 general commercial use |
| Residential warranty | lifetime |
| Commercial warranty | 5 years |

Warranty conditions on www.berryalloc.com.

composition

| | |
|---------------|----------------------------------------------------------|
| Surface layer | Direct laminated paper, impregnated with melamine resin. |
| Substrate | Moisture resistant High Density Fiberboard (HDF). |
| Backing | Direct laminated paper, impregnated with melamine resin. |

test results

| | | |
|-----------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Abrasion resistance | EN13329 | AC4 (IP≥4000) |
| Impact resistance | EN13329 | Small ball : ≥ 12 N - Big ball : ≥ 750 mm |
| Thickness swelling | EN13329 | 12% (requirement ≤ 18%) |
| Fire resistance | EN14041 | Cfl-S1 |
| Formaldehyde emission | EN14041 | E1 |
| Slip resistance | EN14041 | DS |
| Density | EN323 | 900 kg/m ³ |
| Resistance to staining | EN438 | 5 (groups 1+2) ; 4 (group 3) |
| Effect of a furniture leg | EN424 | No damage (foot type 0) |
| Effect of a castor chair | EN425 | No change in appearance or damage |
| Thermal resistance in combination with underlay Excellence Plus | ISO 8302 | 0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com |

certificates/labels

- DOP : 170-DPLA18-1
UKCA : 170-DPLA22-1
- Sustainability of forests :
PEFC certified (07-31-229)
- Labelling according to French
VOC emission regulation: A+

