

# VIVEWOOD®

## Superior Quality Enamel Paint for Wood & Metal



### DESCRIPTION

VIVEWOOD is a superior quality enamel paint ideal for wooden and metallic surfaces. It is specially formulated for the professional painter, ensuring great hiding power, and a perfect mirror-like finish. Its excellent working and leveling properties along with its great elasticity and final appearance makes it the ideal enamel paint for doors, windows, frames and every wooden construction, as well as metal, whenever a smooth and durable surface is required. Its new special formula enriched with high quality raw materials gives VIVEWOOD strong resistance to adverse weather conditions and air pollution without fading, offering long lasting protection.

Excellent leveling properties

High hiding power

### PRODUCT INFORMATION

**Type:** Alkyd based enamel paint

**Specific gravity:** 0,93-1,24 gr/ml (ISO 2811), depending on shades

**Viscosity:** 7-9 ps (ROTOHINNER DIN 51550, 25°C), depending on shade

**Application method:** Brush, roller

**Thinning:** ready for use or up to 3% v/v with VIVECHROM's BRUSH SOLVENT

**Spreading rates:** About 14-18 m<sup>2</sup> / Lt per coat on previously prepared surfaces

**Drying time:** Touch dry after 3-4 hours and recoatable after 24 hours. Drying time depends on weather conditions (humidity, temperature)

**Colours:** It is available in White gloss, satin, mat. Also it is available through **VIVECHROM's** tinting system **CHROMOSYNTHESIS** in unlimited number of shades in gloss and satin.

**Storage:** Store between 5° to 40° C.

#### VOC (Volatile Organic Compounds)

EU limit value for this product A/d Interior/Exterior trim and cladding paints for wood and metal: 300 g/l (2010). This product contains max 299 g/l VOC.



# VIVEWOOD®

## Superior Quality Enamel Paint for Wood & Metal

### SURFACE PREPARATION

- Surfaces must be clean and dry.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- For wooden surfaces after thorough preparation (filling and coating with putty), use undercoat VELATURA.
- For full antirust protection on metal first apply two coats anticorrosive primer RUST PRIMER.

### APPLICATION

- Surfaces must be rubbed down using a suitable abrasive paper.
- Ready for use. If thinning is necessary, add up to 3% BRUSH SOLVENT.
- Stir well and apply two coats of **VIVEWOOD**.

### AFTER USE


Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with Vivechrom's BRUSH SOLVENT.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Hydrocarbons, alkanes – 1-methoxy-2-propanol • Flammable liquid and vapor • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources • No smoking • Keep container tightly closed • Do not get in eyes, on skin, or on clothing • IF INHALED: Remove person to fresh air and keep comfortable for breathing • Call a POISON CENTER or doctor/physician if you feel unwell • Keep cool • Dispose of contents and container in accordance with all local, regional, national or international regulations • Repeated exposure may cause skin dryness or cracking • Contains OIT. May produce an allergic reaction • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Poison Control Center for Greece: +302107793777 / for Cyprus: 1401



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



[www.vivechrom.gr](http://www.vivechrom.gr)