

VIVELACK®

Decorative & Protective Wood Varnish



DESCRIPTION

VIVELACK is a coloured decorative and protective wood varnish for interior and exterior use. It is suitable for doors, windows, frames, claddings, and in general for any wooden surface. It has excellent working and levelling properties. It makes an elastic and tough finish that protects and offers to the wood beautiful appearance.

PRODUCT INFORMATION

Protects and decorates

High Elasticity & Durability

Type: Wood varnish based on synthetic resins.

Specific gravity: 0.92±0.02 gr/cm³ (ISO 2811)

Viscosity: 3.5-6 ps (ROTOTHINNER DIN 51550, 25°C)

Application method: Brush, roller.

Thinning: Up to 3% v/v with Vivechrom's BRUSH SOLVENT

Spreading rates: About 12-16m² per litre per coat on previously prepared surfaces.

Drying times: Touch dry after 5 hours and recoatable after 24 hours. Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in colourless gloss and satin in 6 shades in gloss. Also, it is available through Vivechrom's tinting system CHROMOSYNTHESIS in 63 shades.

Storage: Store between 5°C to 40°C.

VOC (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product of category A/e
Interior/exterior trim varnishes and woodstains, including
opaque woodstains: 400g/l (2010).
This product contains max 399g/l VOC.



Our approach to sustainable business
akzonobel.com/sustainability

www.vivechrom.gr



VIVELACK®

Decorative & Protective Wood Varnish

SURFACE PREPARATION

- Surfaces must be clean and dry rubbed down with a suitable abrasive paper.
- On new or bare wood for best protection from fungi apply 1-2 coats of wood preservative VIVEXYL colourless or coloured.
- Treatments such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.
- For maintenance of previously varnished surfaces apply one coat of **VIVELACK**.

APPLICATION

- Thin with up to 3% v/v with BRUSH SOLVENT and stir well before use.
- Apply 2 coats of VIVELACK in gloss or satin finish.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

AFTER USE – WASTE MANAGEMENT

Remove as much paint as possible from brushes and rollers before cleaning.
Clean brushes and equipment with VIVECHROM's BRUSH SOLVENT immediately after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Hydrocarbons, alkanes • Flammable liquid and vapor • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources • No smoking • Keep container tightly closed • Do not get in eyes, on skin, or on clothing • IF INHALED: Remove person to fresh air and keep comfortable for breathing • Call a POISON CENTER or doctor/physician if you feel unwell • Keep cool • Dispose of contents and container in accordance with all local, regional, national or international regulations • Repeated exposure may cause skin dryness or cracking • Contains biocidal product: OIT. May produce an allergic reaction • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Poison Control Center for Greece: 210 7793777 / for Cyprus: 1401



www.vivechrom.gr

Vivechrom Dr STEFANOS D. PATERAS SA
FACTORY & HEAD OFFICES: THESI VATHI PIGADI, 19600 MANDRA ATTICA, GREECE TEL.:+30 210 5538700, FAX:+30 210 5550464
THESSALONIKI: ETHN. ANTISTASEOS 114, 55134 KALAMARIA, TEL.:+30 2310 450000, FAX:+30 2310 493984

2/2

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**