

TECHNICAL DATA SHEET

Issue Date: 23/11/2020

13th Edition

RUST PRIMER

Anticorrosive Primer for Metallic Surfaces



DESCRIPTION

RUST PRIMER is a quick drying powerful anticorrosive primer which contains non toxic anticorrosive pigments. It is necessary for the protection of metallic surfaces such as vehicles, machinery, rails and any ferrous structure. It has strong adhesion and high elasticity.

Strong adhesion

High elasticity

PRODUCT INFORMATION

Type: Alkyd based anticorrosive primer. **Application method:** Brush, roller. **Specific gravity:** 1,51±0.02 gr/ml.

Thinning: 5-10% v/v with VIVECHROM's BRUSH SOLVENT.

Spreading rates: About 13 m² per litre on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 8 hours. Drying time depends on weather

conditions (humidity, temperature).

Colours: It is available in grey and brown. **Storage:** Storage: Store between 5° to 40° C.

VOC (Volatile Organic Compounds)

EU limit value for this product category A/i one-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC.









www.vivechrom.gr





RUST PRIMER

Anticorrosive Primer for Metallic Surfaces

SURFACE PREPARATION

- Surfaces must be dry and clean from grease, dirt and rust and be thoroughly rubbed down using a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

APPLICATION

- Surfaces must be rubbed down using a suitable abrasive paper.
- Add up to 5-10% BRUSH SOLVENT by Vivechrom.
- Stir well and apply one or two coats of RUST PRIMER.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with AIR-GUN SOLVENT or THINNER 600 GENERAL USAGE by Vivechrom.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Hydrocarbons, n-butyl acetate. • Flammable liquid and vapour • May cause drowsiness or dizziness • Harmful to aquatic life with long lasting effects • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Keep away from heat, sparks, open flames and hot surfaces. - No smoking • Keep container tightly closed • IF INHALED: Remove person to fresh air and keep comfortable for breathing • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Avoid release to the environment • Dispose of contents and container in accordance with all national regulations • Repeated exposure may cause skin dryness or cracking • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Poison Control Center for Greece: +302107793777 / for Cyprus: 1401



STIR WELL BEFORE USE - PROTECT FROM FROST DO NOT APPLY AT TEMPERATURES UNDER 10°C.









www.vivechrom.gr