

# ASTARI ALOUMINIΟΥ & GALVANIZE®

Special Primer for Non Ferrous Metals



## DESCRIPTION

**ASTARI ALOUMINIΟΥ & GALVANIZE** is a special primer, with strong adhesion on non-ferrous metals such as aluminium and galvanized surfaces. It is also suitable for stainless steel and copper. It also provides antirust protection, dries quickly and features high elasticity and very good levelling properties.

## PRODUCT INFORMATION

**Type:** Primer based on special synthetic resins.

**Specific gravity:** 1.23 – 1.25 gr/cm<sup>3</sup> (ISO 2811).

**Viscosity:** 6-8 ps (ROTOTHINNER DIN 51550, 25 OC).

**Application method:** Brush, roller.

**Thinning:** Up to 3% v/v with VIVECHROM's BRUSH THINNER.

**Spreading rates:** About 12 m<sup>2</sup> per litre on previously prepared surfaces.

**Drying times:** Touch dry after 30 minutes and recoatable after 16 hours. Drying time depends on weather conditions (humidity, temperature).

**Colours:** It is available in grey.

**Storage:** Storage: Store between 5° to 40° C.

**Strong adhesion**

**Dries quickly**

### VOC (Volatile Organic Compounds)

EU limit value for this product of category A/i one-pack performance coatings: 500g/l (2010). This product contains max 499g/l.





# ASTARI ALOUMINIYOU & GALVANIZE®

Special Primer for Non Ferrous Metals

## SURFACE PREPARATION

- Metallic surfaces must be dry and clean from grease, dirt and rust and be thoroughly rubbed down using a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

## APPLICATION

- For freshly galvanized surfaces, a very good sanding is needed.
- Thin up to 3% v/v with VIVECHROM'S BRUSH THINNER.
- After the preparation of the surface, apply one coat of ASTARI ALOUMINIYOU & GALVANIZE. When it is completely dry, it can be sanded with a suitable abrasive paper, ensuring stronger adhesion and better leveling for the finish paint.

## AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Naphtha (petroleum), hydrotreated heavy

- Flammable liquid and vapour • May cause drowsiness or dizziness • Harmful to aquatic life with long lasting effects • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Keep container tightly closed • IF INHALED: Remove person to fresh air and keep comfortable for breathing • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Avoid release to the environment • Dispose of contents and container in accordance with all national regulations.

Poison Center: +30210 7793777



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



[www.vivechrom.gr](http://www.vivechrom.gr)