

VELATURA

Undercoat for Enamel Paints



DESCRIPTION

VELATURA is an alkyd-based undercoat for enamel paints with a new formulation that provides very easy sanding properties. It is suitable for interior and exterior wooden surfaces. It presents high hiding power and whiteness and combines excellent levelling and working properties. It is recoated with the superior quality enamel paint VIVEWOOD by VIVECHROM.

PRODUCT INFORMATION

Type: Alkyd based undercoat for enamel paints.

Application method: Brush, roller.

Thinning: Ready for use or add up to 4% v/v with VIVECHROM's BRUSH SOLVENT.

Spreading rates: About 14-18 m² per litre on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 16 hours. Drying time depends on weather conditions (humidity, temperature).

Colours: It is available in white and in selected number of shades through VIVECHROM's tinting system CHROMOSYNTHESIS.

Storage: Store between 5° to 40° C.

Very easy sanding properties

High hiding power

VOC (Volatile Organic Compounds)

EU limit value for this product category A/d Interior/exterior trim and cladding paints for wood and metal: 300g/l (2010). This product contains max 299g/l VOC





VELATURA

Undercoat for Enamel Paints

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt and grease and bethoroughly rubbed down using a suitable abrasive paper.
- Wooden surfaces' imperfections are coated with VIVECHROM' s AKRILIKOS STOKOS OIKODOMON.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

APPLICATION

- Ready for use. Add up to 4% BRUSH SOOLVENT by Vivechrom.
- Stir well and apply two coats of VELATURA. When it is completely dry sand with a suitable abrasive paper to give an even surface onto which the finish coat is applied.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT by Vivechrom.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Flammable liquid and vapour • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Keep container tightly closed • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Poison Control Center for Greece: +30210 7793777 / for Cyprus: 1401



**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**

