

EXTRA NEOCHROM

Excellent Quality Enamel Paint for Metal & Wood



DESCRIPTION

EXTRA NEOCHROM is a full gloss, highly durable enamel paint with superior gloss and colour retention, which provides longlasting protection and beauty. It is suitable for all interior and exterior metallic and wooden surfaces. It forms a hard and flexible finish with exceptional durability to adverse weather conditions and atmospheric pollution as well as to washing. It has excellent working and levelling properties and great hiding power.

Exceptional protection

Perfect decorative finish

PRODUCT INFORMATION

Type: Alkyd based enamel paint.

Specific gravity: 0,95 -1,17 gr/cm³ (ISO 2811) depending on the shade.

Viscosity: 6-8 ps (ROTOTHINNER DIN 51550, 25 °C).

Application method: Brush, roller.

Thinning: Ready for use

Spreading rates: About 13-16m² per litre on previously prepared surfaces.

Drying time: Touch dry after 5 hours and recoatable after 24 hours. Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in 50 shades in gloss finish, and Black mat.

Storage: Store between 5 ° C to 40 ° C.

VOC (Volatile Organic Compounds)

EU limit value for this product of category A/d Interior/exterior trim and cladding paints for wood and metal: 300g/l (2010). This product contains max 299g/l.





EXTRA NEOCHROM

Excellent Quality Enamel Paint for Metal & Wood

SURFACE PREPARATION

- Surfaces must be clean and dry.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- For metal surfaces that require antirust protection use anticorrosive primer RUST PRIMER
- For wooden surfaces after thorough preparation (scraping knots, filling and coating with putty) use undercoat VELATURA.

APPLICATION

Apply 2 coats of EXTRA NEOCHROM.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT by Vivechrom.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains Naphtha (petroleum), hydrotreated heavy - Hydrocarbons, alkanes • Flammable liquid and vapor • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources • No smoking • Keep container tightly closed • Do not get in eyes, on skin, or on clothing • IF INHALED: Remove person to fresh air and keep comfortable for breathing • Call a POISON CENTER or doctor/physician if you feel unwell • Keep cool • Dispose of contents and container in accordance with all local, regional, national or international regulations • Repeated exposure may cause skin dryness or cracking • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Poison Control Center for Greece: +302107793777 / for Cyprus: 1401



**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr