

ELASTIKOS STOKOS

Flexible putty for cracks & joints



PRODUCT INFORMATION

Type: Elastomeric acrylic putty.
Application method: Knife.
Thinning: Ready for use
Colours: It is available in white
Storage: Store between 5°C to 40°C

DESCRIPTION

ELASTIKOS STOKOS is a very flexible acrylic putty. It is suitable for the filling of cracks and joints on walls and roofs. It has very good adhesion and UV and alkali resistance. It follows easily the contractions and expansions of cracks and joints, maintaining its flexibility in surfaces such as cement, concrete, plaster, bricks.

Very Good Adhesion

Elasticity and resistance to weather conditions

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- If needed, cracks are enlarged with mechanical equipment and primed with ASTARI VIVEDUR, thinned up to 20% with VIVECHROM's BRUSH SOLVENT.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.



ELASTIKOS STOKOS

Flexible putty for cracks & joints

APPLICATION

- It is applied without thinning by knife .
- For cracks of width and depth more than 10mm, a polyurethane cord is put into the gap which is filled up with **ELASTIKOS STOKOS** right to the top. Cracks smaller than 10mm are sealed with **ELASTIKOS STOKOS**.
- Apply the material and let it dry at temperatures between 10°C to 35°C.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains Isothiazolinone compounds. May produce an allergic reaction. Safety data sheet available on request • Do not empty into drains • Dispose of contents and container in accordance with all national regulations. Poison Center: +30210 7793777

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr