

#### TECHNICAL DATA SHEET

Issue Date: 18/02/2022

3rd Edition

## MASONRY ACRYLIC PUTTY

**Pre-Paint** 



#### **DESCRIPTION**

**ACRYLIC MASONRY PUTTY** is a white masonry acrylic putty for interior and exterior use. It is suitable for filling and coating of plaster or concrete and for wood. It has excellent working, filling and levelling properties. It dries fast without cracking and is easy to sand giving a smooth and durable surface without imperfections.

#### **Interior and Exterior use**

# Excellent working and filling properties

#### PRODUCT INFORMATION

Type: Water based acrylic putty.
Application method: Knife.
Thinning: Ready for use

**Spreading rates:** About 2-3 m<sup>2</sup> per kilo on previously prepared surfaces.

Drying times: touch dry after 1 hour and can be sanded after 3 hours. Drying time depends on

weather conditions (humidity, temperature) **Storage:** Store between 5°C to 40°C

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.





www.vivechrom.gr





## MASONRY ACRYLIC PUTTY

**Pre-Paint** 

## **APPLICATION**

- It is applied without thinning by knife and it can be sanded after 3 hours using a suitable abrasive paper
- It can be recoated with emulsion or solvent based paints.

### AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of the reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Poison Center for Greece: +30210 7793777 / For Cyprus: 1401

STIR WELL BEFORE USE - PROTECT FROM FROST DO NOT APPLY AT TEMPERATURES UNDER 10°C.





www.vivechrom.gr