

# ASTARI VIVEDUR®

## Waterproofing Acrylic Undercoat



### DESCRIPTION

**ASTARI VIVEDUR** is a high quality clear waterproofing acrylic solvent-based undercoat, with strong adhesion and high penetration for surfaces painted with plastic and acrylic paints. It is a binding primer that stabilizes the surfaces and reinforces the adhesion of the final paint. It is highly recommended as a primer for emulsion paints and acrylic paints, textured finish, masonry paints and waterproofing coatings. It is the perfect primer for old and new porous surfaces such as plaster, concrete, bricks, surfaces coated with lime or low quality paints. It provides water resistant surfaces with vapour permeability. It is superior over linseed oil, as it has very short drying time and doesn't cause yellowing to the finishing paints.

**Strong adhesion and high penetration**

**Stabilizes the surfaces**

**Ideal for walls and roofs**

### PRODUCT INFORMATION

**Type:** Solvent based acrylic undercoat.

**Application method:** Roller, brush or spray gun.

**Thinning:** Walls: Up to 100% with VIVECHROM's BRUSH SOLVENT.

Roofs: Up to 20% with VIVECHROM's BRUSH SOLVENT.

**Spreading rates:** Walls: About 13-15 m<sup>2</sup>/lt per coat, depending on thinning and surface absorption.

Roofs: About 8-10 m<sup>2</sup>/lt per coat, depending on thinning and surface absorption.

**Drying times:** Touch dry after 1 hour and recoatable after 4 hours. Drying time depends on weather conditions (humidity, temperature).

**Storage:** Store between 5° to 40° C.

#### VOC (Volatile Organic Compounds)

EU limit value for this product category A/h  
Binding primers: 750 g/l (2010). This product contains  
max 730 g/l VOC.





## ASTARI VIVEDUR® Waterproofing Acrylic Undercoat

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- For roofs fill cracks and joints with STOKOS VIVEDUR.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

### APPLICATION

- Stir well before use.
- For walls apply one coat of **ASTARI VIVEDUR** thinned up to 100% with Vivechrom's BRUSH SOLVENT and for roofs apply one coat of **ASTARI VIVEDUR** thinned up to 20% with Vivechrom's BRUSH SOLVENT.
- Ensure that the coat of ASTARI VIVEDUR creates the appropriate film thickness.
- Ensure good ventilation during application and drying.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

### AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with BRUSH SOLVENT.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WARNING. Contains - Naphta (petroleum), hydrotreated heavy • Flammable liquid and vapour • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Repeated exposure may cause skin dryness or cracking • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Lift with care - gross weight exceeds 10kg.  
Poison Center: +30210 7793777



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**

