

VIVEDUR MULTIPRIMER ECO

Nanotechnology Premium Water Based Primer



DESCRIPTION

VIVEDUR MULTIPRIMER ECO is silicone acrylic Nanotechnology water based primer, for exterior and interior walls. It is micronized and therefore has increased penetration and stronger adhesion offering excellent cohesion, enhancing porous surfaces such as plaster, concrete, gypsum board, cement boards, stucco, hydrochroma. It is hydrophobic, waterproof and breathable and has very good alkali resistance. It prevents migration of salts from the wall to the top paint film. It has excellent levelling properties and spreads wonderfully. It is an ideal ecological water based primer for surfaces painted with acrylic or plastic water based paints.

Excellent adhesion & penetration

Prevents migration of salts

Superior cohesion

PRODUCT INFORMATION

Type: Nanotechnology silicone acrylic water based primer.

Application method: Brush, roller, airless spray.


Thinning: Thin with clean water up to 50% for exterior surfaces and up to 100% for interior surfaces and stir well before use.

Spreading rates: Exterior surfaces (13-15 m²/Lt) and interior surfaces (16-20 m²/Lt)

Drying times: Touch dry after 1 hour and recoatable after 2 hours. Drying time depends on weather conditions (humidity, temperature).

Storage: Store between 5° to 35° C.

VOC (Volatile Organic Compounds)
EU limit value for this product category A/h
Binding primers: 30 g/l (2010). This product
contains max 3 g/l VOC.



VIVEDUR MULTIPRIMER ECO

Nanotechnology Premium Water Based Primer



SURFACE PREPARATION

- Surfaces must be clean, dry and free of defective or poorly adhesive materials, dirt, grease and salts.
- Treatments such as sanding may generate hazardous dust. Wet sanding/flattening should be used wherever possible. Work in a well-ventilated area. Use suitable personal protection equipment.
- New very alkaline surfaces of concrete or plaster must be primed after about a month.
- To fill and coat the surfaces: Use Vivechrom's STOKOS SPATOULARISMATOS.

APPLICATION

- Thin with clean water up to 50% for exterior surfaces (13-15 m²/Lt) and up to 100% for interior surfaces (16-20 m²/Lt) and stir well before use.
- Apply one coat of **VIVEDUR MULTIPRIMER ECO**.
- Use suitable respiratory protective equipment when using airless spray.
- Application and drying at a temperature of 10 ° C to 35 ° C.
- Minimize paint wastage by estimating how much paint you will need.


AFTER USE

- Remove as much paint as possible from brushes and rollers before cleaning.
- Clean brushes and equipment with water and detergent solution after use.
- Do not put residual paint down the kitchen sink or toilet, or into a waste bin.
- Unused paint requires specialist handling for safe environmental disposal and that it should not therefore be thrown away with or commercial waste. Advice regarding disposal and collection should be sought from the local authority.
- Recover unused paint for re-use.
- Reuse of paint can effectively minimize the products' life cycle environmental.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand
 • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell
 • Contains 1,2-benzisothiazol- 3(2H)-one. May produce an allergic reaction • Do not empty into drains
 • Dispose of contents and container in accordance with all national regulations • Emergency Tel. Number of Official Advisory Body: +30 210 7793777.

**STIR WELL BEFORE USE - PROTECT FROM FROST
 DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr