

VIVEDUR® BLOCK

Acrylic Water Based Stain Stopping Undercoat



DESCRIPTION

VIVEDUR BLOCK is a white, acrylic stain stopping waterbased undercoat, suitable for all interior and exterior masonry surfaces. It seals and covers stains of smoke, nicotine, yellowness, watersoluble felt-tip pen, coffee, juice, old dampness, and other dirt. It has great hiding power, high spreading and strong adhesion. It is ammonia free and has low odour. It seals the stains and prevents their migration on the final coat, while, at the same time, it allows the surface to breath, keeping humidity away. It is easy to apply and it dries fast. It gives a flat, mat surface, providing an exceptional finish for the final coat. Recoatable with all waterbased emulsion and acrylic paints.

High Hiding Power

Seals and covers stains

For nicotine, smoke & yellowness

PRODUCT INFORMATION

Type: Acrylic waterbased undercoat.

Specific gravity:

Viscosity:

Application method: Brush, roller or airless spray.

Thinning: Up to 10% with clean water.

Spreading rates: About 11m² per litre per coat on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 2 hours. Drying time depends on weather conditions (humidity, temperature).

Colours: It is available in White.

Storage: Store between 5° to 40° C.

VOC (Volatile Organic Compounds)

EU limit value for this product category A/a
Interior matt walls and ceilings (Gloss <25@60°): 30 g/l
(2010). This product contains max 28 g/l VOC.



www.vivechrom.gr



VIVEDUR® BLOCK

Acrylic Water Based Stain Stopping Undercoat

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- To fill and coat the surfaces: Use VIVECHROM's putty NEOPAL STUCCO.

APPLICATION

- Thin up to 10% with clean water and stir well before use. It is preferable to use it undiluted on heavily soiled surfaces.
- Apply 1-2 coats of **VIVEDUR BLOCK**. Can be recoatable in 2 hours but for soiled surfaces, it is strongly recommended to recoat 24 hours later, or even more, in order to achieve better dirt blocking.
- Ensure good ventilation during application and drying.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.

AFTER USE

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Poison Center for Greece: +30210 7793777 / For Cyprus: 1401

Lift with care – gross weight exceeds 10 kg.

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr