

VIVELATEX®

Bonding & Waterproofing Latex



DESCRIPTION

VIVELATEX is an acrylic bonding and waterproofing latex, which significantly improves the properties of cement mortars. It increases adhesion to any substrate. It improves elasticity and waterproofing, preventing shrinkage and hairline cracks in screeds and coatings. It also improves the water retention and workability, and protects fresh concrete against premature dehydration. It is an ideal admixture for thin cement layers and plasters, floor screeds, smoothing and repairing mortars and reinforcement in tile adhesives. It can be also used as a primer for paints and roof waterproofing materials and mainly for waterproofing in foundation materials in construction.

Improves adhesion and waterproofing

For all cement mortars

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering materials, dirt, grease and salts. Moisten cementitious substrates to saturation.
- Treatments such as dry sanding will generate dust. Wet sanding should be used wherever possible. Work in well ventilated areas. Use appropriate means for respiratory protection.

VOC (Volatile Organic Compounds)

EU limit value for this product category A/h Binding primers: 30g/l (2010). This product contains max 5g/l VOC.





VIVELATEX®

Bonding & Waterproofing Latex

APPLICATION

VIVELATEX Proportions:

- STOKOS SPATOULARISMATOS of Vivechrom: 10% w/w VIVELATEX and 30% w/w water.
- Plasters: In thick / lath 2-5% w/w on cement. In fine plaster finishing 5-10% w/w.
- Mortars: Up to 20% of cement.
- As a primer: Dilute with water for horizontal surfaces 100% -200% and vertical 200% -300%.
- Stir first VIVELATEX with water and then add the solids, such cement, sand etc.
- Stir until homogeneous mixture, preferably with a mechanical stirrer.
- Application and drying at a temperature from 10 ° C to 35 ° C.
- Storage: At a temperature of 5 ° C to 40 ° C.

AFTER USE – WASTE MANAGEMENT

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains biocidal product: 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations.

Poison Center for Greece: +30210 7793777 / For Cyprus: 1401

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



www.vivechrom.gr