

DECLARATION OF PERFORMANCE
No. EP - REFIXCEM PRO

1. Unique identification code of the product-type: **REFIXCEM PRO**
2. Intended use/es: **Concrete repair product (R4-PCC), for non-structural repair, for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Compressive strength:	Class R4	EN 1504-3:2005
Chloride ion content:	≤ 0,05%	
Adhesive Bond:	≥ 2,0 MPa	
Carbonation resistance:	Pass	
Elastic modulus:	≥ 20 GPa	
Thermal compatibility: - Freeze-Thaw: - Thunder Shower: - Dry cycling:	≥ 2 MPa ≥ 2 MPa ≥ 2 MPa	
Capillary absorption:	≤ 0,5 kg/m ² min ^{0,5}	
Dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.



22

EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
Industrial park of Prosotsani, 66200 Drama, Greece

DoP No. EP - REFIXCEM PRO

EN 1504-3

REFIXCEM PRO

Concrete repair product (R4-PCC), for non-structural repair, for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.

Compressive strength:	Class R4
Chloride ion content:	≤ 0,05%
Adhesive Bond:	≥ 2,0 MPa
Carbonation resistance:	Pass
Elastic modulus:	≥ 20 GPa
Thermal compatibility:	
- Freeze-Thaw:	≥ 2 MPa
- Thunder Shower:	≥ 2 MPa
- Dry cycling:	≥ 2 MPa
Capillary absorption:	≤ 0,5 kg/m ² min ^{0,5}
Dangerous substances	see SDS