

DECLARATION OF PERFORMANCE
No. PTS - MARMOFINISH FW EXTRA FINE

1. Unique identification code of the product-type: **MARMOFINISH FW EXTRA FINE**
2. Intended use/es: **Concrete repair product for non-structural repair (R1-PCC), for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT “MARMODOM”
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Compressive strength:	Class R1	EN 1504-3:2005
Chloride ion content:	≤ 0.05%	
Adhesive Bond:	≥ 0.8 MPa	
Thermal compatibility: - Freeze-Thaw:	There is no visual surface defects and cracks.	
Capillary absorption:	≤ 0.5 kg*m ⁻² *h ^{-0,5}	
Reaction to fire	NPD	
Dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.



17

EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
Industrial park of Prosotsani, 66200 Drama, Greece

DoP No. **PTS - MARMOFINISH FW EXTRA FINE**

EN 1504-3

MARMOFINISH FW EXTRA FINE

Concrete repair product for non-structural repair (R1-PCC),
for uses with low performance requirements in buildings and civil engineering works not subject
to reaction to fire regulations.

Compressive strength:	Class R1
Chloride ion content:	≤ 0.05%
Adhesive Bond:	≥ 0.8 MPa
Thermal compatibility: - Freeze-Thaw:	There is no visual surface defects and cracks.
Capillary absorption:	≤ 0.5 kg*m ⁻² *h ^{-0,5}
Reaction to fire:	NPD
Dangerous substances	see SDS