

DECLARATION OF PERFORMANCE

No. KP-ELASTIC PRO

1. Unique identification code of the product-type: **ELASTIC PRO**
2. Intended use/es: **Improved cementitious tile adhesive (C2TES1), for internal and external wall and floor tiling.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**
INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.
4. System/s of AVCP: **System 3**
System 4 (Reaction to fire)
5. Harmonised standard: **EN 12004-1:2017**
Notified body/ies: **NB 1289, Lucideon**

6. Declared performance/s:

| Essential characteristics | Performance | Harmonised Technical Specification |
|-----------------------------------------|-----------------------------------------------------------------------------------|------------------------------------|
| Reaction to Fire: | Class E | EN 12004-1:2017 |
| Bond strength: | expressed as: initial tensile adhesion strength $\geq 1.0 \text{ N/mm}^2$ | |
| Durability against: | expressed as: | |
| climate/heat ageing action: | - tensile adhesion strength after heat ageing $\geq 1.0 \text{ N/mm}^2$ | |
| water/humidity action: | - tensile adhesion strength after water immersion $\geq 1.0 \text{ N/mm}^2$ | |
| freeze-thaw cycles: | - tensile adhesion strength after freeze-thaw cycles $\geq 1.0 \text{ N/mm}^2$ | |
| Release of dangerous substances: | See SDS | |

Appropriate Technical Documentation: included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 2010/81/EU.

Organic material < 20% by weight

Maximum layer thickness 20 mm

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Athanasios Lazaridis
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 16/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

| | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  1289 | |
| 22 | |
| EAGLE S.A. / AETOS A.E. INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" Industrial park of Prosotsani, 66200 Drama, Greece | |
| DoP No.: KP-ELASTIC PRO EN 12004-1 | |
| ELASTIC PRO Improved cementitious tile adhesive (C2TES1), for internal and external wall and floor tiling. | |
| Reaction to Fire: | Class E |
| Bond strength: | expressed as: initial tensile adhesion strength $\geq 1.0 \text{ N/mm}^2$ |
| Durability against: climate/heat ageing action: water/humidity action: freeze-thaw cycles: | expressed as: - tensile adhesion strength after heat ageing $\geq 1.0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1.0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1.0 \text{ N/mm}^2$ |
| Release of dangerous substances: | See SDS |