

**DECLARATION OF PERFORMANCE**  
**No. PTS - MARMOFINISH FW**

1. Unique identification code of the product-type: **MARMOFINISH FW**
2. Intended use/es: **Concrete repair product for non-structural repair (R2-PCC), for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.**
3. Manufacturer: **EAGLE S.A. / AETOS A.E.**  
**INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY**  
**BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"**  
**INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.**
4. System/s of AVCP: **System 4**
5. Harmonised standard: **EN 1504-3:2005**  
Notified body/ies: **No tasks for the notified body**
6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
<b>Compressive strength:</b>	Class R2	EN 1504-3:2005
<b>Chloride ion content:</b>	≤ 0.05%	
<b>Adhesive Bond:</b>	≥ 2.0 MPa	
<b>Thermal compatibility: - Freeze-Thaw:</b>	≥ 1.5 MPa	
<b>Capillary absorption:</b>	≤ 0.5 kg*m <sup>-2</sup> *h <sup>-0,5</sup>	
<b>Reaction to fire</b>	NPD	
<b>Dangerous substances</b>	See SDS	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis  
Q.C. / R&D Manager



At: Prosotsani, Drama, Greece

on 12/05/23

**REACH information:** the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.

<b>CE</b>	
<b>15</b>	
<b>EAGLE S.A. / AETOS A.E.</b> <b>INDUSTRIAL, COMMERCIAL &amp; TRANSPORT COMPANY</b> <b>BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"</b> <b>Industrial park of Prosotsani, 66200 Drama, Greece</b>	
DoP No. <b>PTS - MARMOFINISH FW</b> <b>EN 1504-3</b>	
<b>MARMOFINISH FW</b>	
Concrete repair product for non-structural repair (R2-PCC), for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.	
<b>Compressive strength:</b>	Class R2
<b>Chloride ion content:</b>	≤ 0.05%
<b>Adhesive Bond:</b>	≥ 2.0 MPa
<b>Thermal compatibility: - Freeze-Thaw:</b>	≥ 1.5 MPa
<b>Capillary absorption:</b>	≤ 0.5 kg*m <sup>-2</sup> *h <sup>-0,5</sup>
<b>Reaction to fire:</b>	NPD
<b>Dangerous substances</b>	see SDS