



Gypsum Board Datasheet

05-2019

Knauf Gypsum Wall Board (GW-R)

Knauf Regular Gypsum Boards are ASTM C 1396 compliant gypsum boards specifically designed for use where high quality gypsum boards requirements are essential to achieve the desired interior design intent.



Knauf Gypsum Wall Board (GW-R)

Product Description

Knauf Regular Gypsum Boards are ASTM C 1396 compliant gypsum boards specifically designed for use where high quality gypsum boards requirements are essential to achieve the desired interior design intent.

Fields of Application

Knauf Regular Gypsum Boards are the essential component for standard lightweight drywall constructions and are used as the cladding component for:

- Drywall partitions using metal or wooden frames
- Suspended ceilings using metal or wooden frames
- Furring and wall linings
- Prefabricated building units
- Drylining blockwork/concrete walls using dot and dab of a gypsum based bonding compound

Properties

- Lightweight constructions
- Easy, fast and dry application
- Good sound insulation performance
- Good fire protection performance
- A material that breathes and balances room climate and humidity levels
- Environmental friendly
- Limitless design options

Technical Data

Board Dimensions:

Thickness: 12.7 mm / 15.9 mm

Width: 1220 mm

Length: 2400 or 3000 mm

* Special sizes are available upon request.

Board Weights (average values):

12.7 mm approx. 9.7 kg / m²

15.9 mm approx. 12.3 kg / m²

Total Water Absorption:

N/A

Nail Pull Resistance (Method B):

12.7 mm : > 343 N

15.9 mm : > 387 N

Flexural Strength (Method B):

	12.7 mm	15.9 mm
--	---------	---------

Parallel	> 160 N	> 205 N
----------	---------	---------

Perpendicular	> 476 N	> 654 N
---------------	---------	---------

Edge Detail:

Square Edge (SE) 

Tapered Edge (TE) 

Appearance:

Ivory Paper Liner

Standards and Codes:

ASTM C1396 / C1396M - 09a - Section 5

ASTM E84 - Flame Spread = 10

Intertek listed under CSI code: 09 29 00

Note:

Please contact our sales department for inquiries about storage and packing.

Knauf Head Office

▶ Phone: +971 4 337 7170

▶ Fax: +971 4 334 9659

▶ P.O.Box: 112871, Dubai

▶ info@knauf.ae

Knauf Manufacturing Plant

P.O.Box 50006
Ras Al Khaimah, U.A.E.
Tel: +971 7 268 9837
Fax: +971 7 221 5301

Knauf Gypsum India Pvt.Ltd

No. 8 - C, 8th Floor Commercial Complex
Doshi Tower, New No. 205, (Old No.156)
Poonamallee High Road,
Kilpauk Chennai - 600010
Tamil Nadu, India
Tel: +91 44 49580000
Fax: +91 44 49575300

Disclaimer:

The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of its employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to rely on it. In particular, readers must obtain appropriate independent advice on the use in specific structures, insulations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification.

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.